

SPECIFICATIONS

IP Camera:

Sensor: 1/3", 4.0 megapixel, progressive scan, CMOS

Shutter: Auto/Manual, 1 ~ 1/100000s

Lens Type: 4.0mm

IR Range: Up to 30m (98ft) IR range

IR On/Off Control: Auto/Manual

Video Compression: H.265, H.264, MJPEG

Frame Rate: Main Stream: 4MP (2688*1520), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps;

White Balance: Auto/Outdoor, etc

Digital Noise Reduction: 2D/3D DNR

Events: Basic Detection Cross line, intrusion(based on human body detection), motion detection

General Function: IP address filtering, access policy, ARP protection, user authentication, HTTP authentication

Network Protocols: IPv4, IPv6, ARP, TCP, UDP, DHCP, RTP, DNS, NTP, FTP, HTTP, HTTPS, 802.1x

User/Host: Up to 32 user

2 user levels: administrator and common user

Security: Password protection, Strong password, HTTPS encryption, Export operation logs, etc.

Network: 1 * RJ45 10M/100M Ethernet

Power: DC 12V±25%, PoE

Power consumption: Max 9.0W

NVR:

IP Video Input: 16-ch

Incoming Bandwidth: 64Mbps

Outgoing Bandwidth: 48Mbps

Protocols: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS

HDMI/VGA Output: HDMI: 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz; VGA: 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz

Recording Resolution: 1080p/960p/720p or more

Audio Output: 1-ch

Synchronous Playback 16-ch

Decoding format: Ultra 265/H.265/H.264

SATA: 1 SATA interface

Capacity: Up to 8TB for each disk (The maximum HDD capacity varies with environment temperature)


VCA Detection by Camera: Intrusion Detection, Cross Line Detection, Enter Area, Leave Area

General Alarm: Motion, Tampering, Human Body Detection, Video Loss


Alert Alarm: IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk

Space Low, Hard Disk Full, Recording/Snapshot Abnormal

Network Interface: 1 RJ45 10M/100M Ethernet Interface


208 1/3/12


गोरखा नगरपालिका
नगर कार्यपालिकाको कार्यालय
बुधौडाँडा, गोरखा
मध्य प्रदेश, नेपाल


गणेश शर्मा अधिकृत

USB Interface: 2 x USB2.0
Power Supply: 12V DC

Media Converter:

Fiber Media Converter
Support 10/100M
Stable performance

POE Switch:

4 port POE and 8 port POE

LAN Cable:

CAT6 LAN Cable

Monitor:

18" Monitor HD


Junction Box


Plastic


Hard Disk

4TB WD Purple

Fiber and Power Cable and accessories


2081/03/12


प्रमुख प्रशासकिय अधिकृत


गोरखा नगरपालिका
नगर कार्यपालिकाको कार्यालय
बुध्रीडाँडा, गोरखा
मण्डवी प्रदेश, नेपाल